

Smart choice for power™

xantrex™

# Xantrex™ Solar Charge Controller XW-MPPT60-150



The Xantrex™ XW Solar Charge Controller is a photovoltaic (PV) charge controller that tracks the electrical maximum power point of a PV array to deliver the maximum available current for charging batteries. When charging, the XW Solar Charge Controller regulates battery voltage and output current based on the amount of energy available from the PV array and state-of-charge of the battery.

The XW Solar Charge Controller can be used with 12, 24, 36, 48, and 60-volt DC battery systems and is able to charge a lower nominal-voltage battery from a higher nominal-voltage array. For example, the XW Solar Charge Controller can charge a 12-volt battery from a 36-volt array. This provides flexibility for installers to use longer wiring runs without compromising efficiency. The XW Solar Charge Controller can be installed in single or multi-unit configurations with a Xantrex XW Hybrid Inverter/Charger or can be used in other solar energy systems where a solar charge controller is needed.

The XW Solar Charge Controller incorporates a dynamic Maximum Power Point Tracking (MPPT) algorithm designed to maximize energy harvest from the PV array. The MPPT constantly adjusts the operating points of the array to ensure it stays on the maximum power point. It does not stop energy harvest to sweep the array like some other competing products. This feature is beneficial in all sunlight conditions, especially in areas with fast moving cloud cover and quickly changing solar conditions.

## Product features

- ▶ Maximum Power Point Tracking (MPPT) delivers maximum available power from PV array to battery bank
- ▶ Integrated PV ground-fault protection
- ▶ Ultra-reliable, convection-cooled design does not require a cooling fan – large, aluminum, die-cast heat-sink allows full output current up to 45°C without thermal derating
- ▶ Selectable two or three stage charging algorithms with manual equalization to maximize system performance and improve battery life
- ▶ Configurable auxiliary output
- ▶ Two-line, 16-character liquid crystal display (LCD) and four buttons for configuration and system monitoring
- ▶ Input over-voltage and under-voltage protection, output over-current protection, and backfeed (reverse current) protection (warning and fault messages appear on LCD when unit shuts down as a protective measure)
- ▶ Over-temperature protection and power derating when output power and ambient temperature are high
- ▶ Battery Temperature Sensor (BTS) included – automatically provides temperature-compensated battery charging
- ▶ Xanbus™-enabled network communications protocol (developed by Xantrex)
- ▶ Communicates settings and activity to other Xanbus™-enabled devices, such as the XW Hybrid Inverter/Charger, the XW System Control Panel (XW SCP), XW Automatic Generator Start (XW AGS), and other XW Solar Charge Controllers
- ▶ Five-year warranty (10 year warranty optional)

## Xantrex Technology Inc.

### Headquarters

8999 Nelson Way  
Burnaby, British Columbia  
Canada V5A 4B5  
800 670 0707 Toll Free  
604 420 1591 Fax

Xantrex Technology, S.L.  
Bac de Roda 52, edificio A  
08019 Barcelona, Spain  
+34 93 433 8350 Tel  
+34 93 433 8351 Fax

europesales@xantrex.com

[www.xantrex.com](http://www.xantrex.com)

## Xantrex™ XW Solar Charge Controller

**Electrical Specifications**

Nominal battery voltage	12, 24, 36, 48, 60 Vdc
Maximum PV array voltage (operating)	140 Vdc
Maximum PV array open circuit voltage	150 Vdc
Array short-circuit current	60 Adc maximum
Maximum and minimum wire size in conduit	#6 AWG to #14 AWG
Total power consumption while operating	2.5 W (tare)
Charger regulation method	Three-stage (bulk, absorption, float) Two-stage (bulk, absorption)

**Mechanical Specifications**

Dimensions (H × W × D)	14 ½ × 5 ¾ × 5 ½" (368 × 146 × 138 mm)
Weight (controller only)	10.75 lb (4.8 kg)
Weight (shipping)	17.6 lb (8 kg)
Shipping dimensions (H × W × D)	19 × 9 × 9 ¾" (483 × 229 × 350 mm)
Mounting	Vertical wall mount
Standard warranty	Five years (10 years optional)
Part number	865-1030

**Environmental Specifications**

Enclosure type	Indoor, ventilated, sheet metal chassis with 7/8" and 1" (22.22 mm and 27.76 mm) knockouts and aluminum heat-sink
Operating temperature range (full power)	-4 to 113 °F (-20 to +45 °C)
Storage temperature	-40 to 185 °F (-40 to +85 °C)
Altitude limit (operating)	Sea level to 15,000 feet (4572 m) @ 15 °C

**Regulatory Approvals**

CSA certified to CSA 107.1, UL 1741 FCC Class B and Industry Canada, CE

**Optional Accessories**

XW System Control Panel	865-1050
XW Automatic Generator Start	865-1060
Network cables:	
3 feet (0.9 m)	809-0935
25 feet (7.6 m)	809-0940
50 feet (15.2 m)	809-0941
75 feet (22.9 m)	809-0942
Network terminator	809-0901 (two per pack)

Specifications subject to change without notice.

For more information on the XW System please visit [www.xantrex.com/xw](http://www.xantrex.com/xw)